

DirectTex® AKUSTICO® NewLife FR

Fields of application

.01 .02 .03 .04 .05 .06 .07 .08 .12

Specifications



606252 172



100 % post-consumer recycled polyester
weave fabrics
PVC-free, recyclable



ca. 155/ 310 cm
ca. 61/ 122 inch
other widths available on request



B-s1, d0 DIN EN 13501-1
NFPA 701



ca. 280 g/m²
ca. 8.3 oz/yd²



ca. 0.65 mm
ca. 650 µm



rolls
50 m
55 yd



Abrasion resistance
DIN EN ISO 12947-2 25.000 tours
category B according to DIN EN14465



Rub fastness
(dry & wet)
DIN EN ISO 105-X12 grade 4 – 5



heat, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub	UVgel
Inside	•	•	•	
Outside	•	•	•	

Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,8 %	1,7 %	•
190°C	1,1 %	2,6 %	
200°C	1,5 %	4,0 %	
210°C	1,9 %	5,7 %	

Certifications



DirectTex® AKUSTICO® NewLife FR

Fields of application

.01 .02 .03 .04 .05 .06 .07 .08 .12



Ref.-Nr.: 506252 113 | Preview print sample



PONGS GROUP GMBH & CO. KG

Bahnhofstraße 21
07919 Pausa-Mühltrorf
Germany

Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of $\pm 5\%$ is valid. Effective: 2022/09